

Declaration of Performance no. 282/CPR



| | |
|--|--|
| Unique identification code of the product-type: | ATLAS GEOFLEX (2023) |
| Intended use or uses: | All internal and external tiling |
| Manufacturer: | Atlas sp. z o.o. Jana Kilińskiego 2 St., 91-421 Łódź, Poland www.atlas.com.pl |
| System or systems of AVCP: | System 3 |
| Harmonised standard: | EN 12004:2007+A1:2012 Notified Body no. 0767 MPA Dresden GmbH Notified Body no. 1487 Sieć Badawcza Łukasiewicz – Instytut Ceramiki i Materiałów Budowlanych |

Declared performance:

| Essential characteristics | Performance |
|--|-------------------------|
| Reaction to fire | A1 A1 _{fl} |
| Bond strength expressed as: <ul style="list-style-type: none"> initial tensile adhesion strength: | ≥ 1.0 N/mm ² |
| Durability of bond strength against climate/heat ageing action expressed as: <ul style="list-style-type: none"> tensile adhesion strength after heat ageing | ≥ 1.0 N/mm ² |
| Durability of bond strength against water/humidity action expressed as: <ul style="list-style-type: none"> tensile adhesion strength after water immersion | ≥ 1.0 N/mm ² |
| Durability of bond strength against freeze-thaw cycles expressed as: <ul style="list-style-type: none"> tensile adhesion strength after freeze-thaw cycles | ≥ 1.0 N/mm ² |
| Release of dangerous substances | NPD |

The performance of the product is in Conformity with the declared performance range. This declaration of performance is issued in accordance to EU Regulation no. 305/2011 under sole responsibility of the manufacturer listed above.

Signed for and on behalf of the manufacturer by Patrycja Stasiak in Łódź, on 18.10.2023.

ATLAS sp. z o.o.
Dyrektor ds. Jakości
Stasiak
Patrycja Stasiak