

Schuller Eh'klar GmbH  
AUSTRIA  
Im Astenfeld 6  
A – 4490 St. Florian  
Tel.(0043) 07224/68 200  
Fax(0043) 07224/68 282  
E-Mail: office@schuller.eu  
www.schuller.eu

**Schuller  
Eh'klar**

St. Florian, 07 July 2025

# FOLI PROTECT

(Articlenumbers: 46402, 46403, 46405, 46413)

## Description:

- Full-surface adhesive cover film for covering glass surfaces, metal, etc.
- The film is not harmful and can be completely recycled

## Technical data:

|                         |                                          |
|-------------------------|------------------------------------------|
| material                | LDPE-Folie                               |
| adhesive                | Environmentally water based acrylic glue |
| strentgh                | 50 my ( $\pm 10\%$ )                     |
| density                 | 0,922 g/m <sup>3</sup>                   |
| weight                  | 36 g/m <sup>2</sup> ( $\pm 10\%$ )       |
| adhesion                | >80 cN/cm (Afera 4001 Glass)             |
| elongation (vertical)   | >200%                                    |
| elongation (horizontal) | >400%                                    |
| UV resistance           | Outdoor 28 days                          |
| application temperatur  | -5°C to +35°C (dry surface)              |

## Application surfaces:

- Glass, aluminium, PVC and stainless steel, wood, ceramic, metal, mirror...

## Application:

- Don't remove the film with sudden movements from the glass surfaces
- The film must be applied to dry and clean surface. The application must be made without fat, water, air bubbles or excessive stretching of the film
- The film must be removed within 4 weeks
- Test adhesion necessary

## Storage:

Storage at room temperature (between 10 ° C and +30 ° C at a relative humidity of 50%). Keep away from direct sunlight and other heat sources. In compliance with the storage conditions, the film can be stored for 6 to 12 months.